EXIDE XPRESS

Sahi Daam, Bhaari Kaam

EXIDE

ADVANTAGES OF MHD BATTERY

CHARACTERISTIC	ADVANTAGES
Polypropylene container with strengthening ribs	Strong and durable. Ability to withstand bumps and vibration.
Factory Charged	Ready for fitment. Eliminates possibility of contamination (because of use of impure acid/water during initial charging in the field). Low self discharge characteristics because of use of high quality acid/water.
Side Vented Design	Top surface of battery remains clean, as such no loss of charge because of surface leakage of current.
Microporous filter disc	Curtails emission of acid fumes thus preventing corrosion of cable clamps or components in the engine compartment.
Magic Eye	Enables state of charge or electrolyte level to be ascertained without having to open the service plugs.
PE/Glassmat Assembly	Enables battery to withstand high vibrations and minimizes possibility of through shorts which cause premature failure of the battery.
Hybrid Design	Enhanced low maintainance characteristics (Topping up requirements in normal working conditions would be once in six months) Ability to withstand high ambient operating conditions as prevalent in India.
Low Internal Resistance	Ability to generate high cranking power during starting. Enables battery to quickly recharge while in use. (The vehicle does not need to drive long distances to ensure full charge of the battery)
Low degradation	Ensure long trouble free service.

EXIDE XPRESS MAINTENANCE FREE RANGE - CONFIRMS TO JISD 5301 - 1999 & IS 14257 - 1995

Battery Type	Part Number	Capacity (Ah)20 HR (Ref)	Maximum Overall Dimention (MM)			Nominal Weight (Kg) Filled	Electrolyte Volume (LTS)	Charging Current (Amps)	CCA at - 18° C as per		Acid Level Indicator	Battery Layout
			L	W	H				IEC	SAE		
MHD 320	FEX0-MHD 320	32	197	129	227	10.2	2.4	2.5	230	280	PRESENT	
MHD 350	FEX0-MHD 350	35	197	129	227	10.9	2.2	2.5	270	332	PRESENT	
MHD 350L	FEX0-MHD 350L	35	197	129	227	10.9	2.2	2.5	270	332	PRESENT	
MHD 600	FEX0-MHD 600	60	260	173	225	17.4	4.8	3.5	256	320	PRESENT	
MHD 700	FEX0-MHD 700	65	260	173	225	18.7	4.4	6.0	400	535	PRESENT	
MHD 700L	FEX0-MHD 700L	65	260	173	225	18.7	4.4	6.0	400	535	PRESENT	
MHD 88	FEX0-MHD 88	88	410	176	233	25.9	6.8	5.5	400	500	PRESENT	
MHD 99	FEX0-MHD 99	99	410	176	233	27.2	6.5	6.5	472	590	PRESENT	
MHD 800	FEX0-MHD 800	80	305	173	225	22.2	4.8	5.0	400	500	PRESENT	
MHD1300	FEX0-MHD1300	130	505	182	257	35.7	8.5	9.0	560	700	PRESENT	
MHD1500	FEX0-MHD1500	150	508	222	257	41.5	11.0	9.0	640	800	PRESENT	
MHD1600*	FEX0-MHD1600	160	508	222	257	43.5	10.2	10.0	688	860	PRESENT	
MHD1800*	FEX0-MHD1800	180	508	222	257	45.5	9.6	11.0	740	920	PRESENT	

Warranty Period

36 Months Pro-rata Warranty	MHD 320, MHD 350, MHD 350L		
18 Months	MHD 600 MHD 700 MHD 700L MHD 800	MHD 88 MHD 99 MHD 1300 MHD 1500	MHD 1600 MHD 1800

MAINTENANCE FREE
EXIDE XPRESS
Sahi Daam
Bhaari Kaam

Head Office : Exide House, 59 E, Chowringhee Road, **Kolkata** - 700020, Tel.: (033) 22832120/ 22832133/ 22832136/22832150/ 22832151/ 22832171/ 22832238 / 22832239, Fax: (033) 22832632/ 22832637. **Northern Regional Office** : Exide House, 3E/1Jhandelwalan Extension, Link Road, **New Delhi** - 110 055, Ph : (011) 23625846/5397/23632907/23627096/7, Fax : (011) 23555703. **Eastern Regional Office** : 6A, Hatibagan Road , Entally, **Kolkata** - 700 014. Ph.: (033) 22458977/22464560/4566, Fax : (033) 22446555. **Western Regional Office :** Exide Industries Limited, Apeejay Chambers, Wallace Street, Fort, **Mumbai** - 400 001. Tel.: 22072188/89/22074918, Fax.: 22078631. **Southern Regional Office** : Exide House, 751 Anna Salai, **Chennai** - 600002. Ph.: (044) 28525070/3703/5349, Fax.: (044) 28528634

This catalogue is issued to provide outline information only and is not deemed to form part of an offer or contract. Our policy is one of continued improvement and we reserve the right to change details without prior notice. **Visit us at** http://www.exidereachout.com

LEAFLET REF: EXIDE/XPRESS/5/2005